

POWERFUL PERFORMANCE FOR THE LONG RUN

Fujitsu Services introduces TeamPoS 3000 XL



If you require a high-performance POS terminal that will grow with your retail business, **Fujitsu's TeamPoS 3000 XL** delivers. This powerful system features Intel® processors and a host of features designed to drive down your total cost of ownership. From standalone point of sale to **mission-critical** applications such as loyalty, merchandising and **customer relationship management**, the TeamPoS 3000 XL meets the demanding needs of today's pervasive retailing environment.

TeamPoS 3000 XL – Key Features

Long term performance Offers powerful architecture and a stable platform based on Intel's embedded roadmap for long term support additionally providing a suitable migration path for existing TeamPoS 2000 customers.

Easy to upgrade Several Intel Celeron® M and Pentium® M processor options let you upgrade as your requirements become more demanding and open architecture design lowers the cost of future upgrades.

Advanced power management Provides an efficient balance of power consumption, CPU utilisation and performance. Reduces your power consumption and allows energy conservation when terminal is inactive.

Unmatched serviceability Components are easy to replace and can be accessed through the front of the unit without removing cables or unstacking peripherals. Ease of maintenance reduces on-site service calls.

Industry-standard design Lower development costs for new and existing systems through compliance with industry standard operating systems, OPOS/JPOS, PC tools and utilities.

System flexibility Compact and standard controllers and extensive peripheral options provide flexibility for location and footprint of system supporting both stacked and dispersed configurations. Additionally a wide choice of peripherals can be supported including legacy (RS232) and futures (USB).

Remote management Industry-standard remote diagnostics and remote management capabilities reduce your help desk calls and service call visits, enabling you to perform maintenance before a device fails.

Environmental compliance Meets RoHS and WEEE compliance standards which protect your investment and ensure a long, useful life.

TeamPoS 3000 XL – Dependable PoS from Fujitsu



ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com



TeamPos® 3000 XL Technical Specifications

<p>Processor</p> <p>Supports Intel 1.3 GHz Celeron M to 2.0 GHz Pentium M processors</p>	<p>Optional I/O</p> <p>Option I: 2 x RS232, +24VDC 3 x RS232, +5 VDC 6 x Powered USB, +12 VDC</p>	<p>Power Supply</p> <p>100 to 240 VAC, 50/60 Hz Auto sensing 270 watts DC output 1 x AC outlet (IEC connector) Fan Alarm</p>
<p>Motherboard</p> <p>Up to 2 MB cache Enhanced Speed Step Technology (Pentium M only)</p> <p>Core chipset: 855GME</p> <p>Integrated Ethernet LAN: 10/100 Mbps with wake-on-LAN support</p> <p>Integrated audio: Sound Blaster compatible</p>	<p>Option II: 3 x Powered USB, +12 VDC</p> <p>Option III: 6 x Powered USB, +12 VDC</p>	<p>Battery backup</p> <p>Optional battery maintains PC environment through power outage Integrated UPS option.</p>
<p>Graphics/Video</p> <p>Integrated video with up to 128 MB of memory Analog/Digital display support Dual independent display support Analog RGB, 15-pin interface Digital DVI, DVI-D interface UXGA support, up to 1600 x 1200 resolution</p>	<p>Memory</p> <p>256MB to 2GB Error Correcting (ECC) memory 2 x 184 pin DIMM slots Double Data Rate (DDR) 333MHz memory</p>	<p>Dimensions</p> <p>Compact: 340 cm x 450 cm x 120 cm 13.4 in. x 18.3 in. x 4.7 in)</p> <p>Standard: 450 cm x 465 cm x 120 cm (17.7 in. x 18.3 in. x 4.7 in.)</p>
<p>Standard I/O Ports</p> <p>2 x PS/2 1 x Audio (in/out) 1 x LAN 10/100 1 x VGA 1 x DVI</p> <p>2 x standard COM (support +5V or 12V) 2 x standard USB (in rear) 2 x additional USB ports (in front) 1 x +24V USB powered (printer) 1 x Cash Drawer (supports up to 2 cash drawers)</p>	<p>Award BIOS</p> <p>Support latest versions of APM, ACPI, WiFm Boot from LAN Local and Remote Flash Password protected P x E</p>	<p>Operating Systems</p> <p>Windows 2000 Windows XP Pro Windows XPe Window Embedded for Point of Sale (WEPOS) Windows Pro Server 2003</p>
	<p>Expansion Slots</p> <p>1 x ½ height PCI Slot 1 x Mini-PCI</p>	<p>Power Management</p> <p>APM 1.2 ACPMI 1.0</p>
	<p>Disk Support</p> <p>Up to 2 SATA (2.5")</p> <p>Removable hard drive with zero insertion connectors for accessibility and ease of maintenance (drives can be replaced without removing cables)</p> <p>Options: CDRW/DVD</p> <p>On board RAID supports RAID 0,1, Auto Recovery</p>	<p>Remote Management</p> <p>WiFm 1.1 DMI 2.0</p>
		<p>Additional Features</p> <p>Plug 'N' Play CPU fan failure alarm Optional Wireless LAN 802.11 a/b/g</p>
		<p>Colour Options</p> <p>Fujitsu Black or Fujitsu White</p>

Specification subject to change



ASK FUJITSU

Contact us on +44 (0) 870 242 7998 or
askfujitsu@uk.fujitsu.com or visit uk.fujitsu.com